

SOLOPANEL

ACOUSTICAL PANELS FOR WALLS & CEILINGS

- ✓ Monolithic, seamless look
- ✓ Coherence between walls and ceiling
- ✓ Wide range of designs











FEATURES

- Unpainted panels
- Wall and ceiling mount
- Jointing and paint on site
- Screw-fixing on steel
- No visible joints after finishing

RECYCLABLE PRODUCT:

- Made of gypsum
- Danish Indoor Climate Labelling
- Product is recyclable and can be reused in the production of new gypsum boards and gypsum tiles
- Repaintable without loss of acoustics

PRODUCT VARIANTS

PERFORATION DESIGN								
PERFORATION MEASURES	G6/18 Circles Ø6mm, c/c 18	G8/18 Circles Ø8mm, c/c 18	G10/23 Circles Ø10mm, c/c 23	G12/25 Circles Ø12mm, c/c 25	G15/30 Circles Ø15mm, c/c 30	Q8/18 Square 8x8mm, c/c 18	G8/12/50 Circles Ø8 & Ø12mm, c/c 50	G12/20/66 Circles Ø12 & Ø20mm, c/c 66
EDGE DESIGN	SIZES, mm							
 UFF EDGE	1188x1998	1188x1998	1196x2001	1200x2000	1200x1980	1188x1998	1200x2000	1188x1980
 MF EDGE	-	1188x1998	1196x2001	1200x2000	-	-	-	1188x1980
PERFORATION %	8.7	15.5	14.8	18.1	19.6	19.8	13.1	19.6
NRC, @ 200mm no mineral wool	0.45	0.60	0.60	0.65	0.65	0.65	0.60	0.65
NRC, @ 200mm + 20mm mineral wool	0.45	0.65	0.65	0.70	0.70	0.70	0.65	0.70
ALPHA-W, @ 200mm no mineral wool	0.45	0.60	0.60	0.65	0.65	0.65	0.60	0.60
ALPHA-W, @ 200mm + 20mm mineral wool	0.50	0.65	0.65	0.70	0.70	0.75	0.65	0.70
PANEL WEIGHT, kg/m ²	8.80	8.10	8.20	7.90	7.80	7.70	8.40	7.80
SURFACE TREATMENT	Front: Unpainted cardboard surface Back: Acoustic felt backing							
SUBSTRUCTURE	Installed on steel (min. 50 mm furring for G6/18, G8/18, G10/23 and Q8/18) (min. 60 mm furring for G12/25, G15/30, G8/15/20 and G12/20/66)							
CERTIFICATES	Danish Indoor Climate Labelling							

PRODUCT PERFORMANCE

FIRE RATING

A2-s1, d0
UL-listed in accordance to R26164

AIR QUALITY

Indoor value: 10 days
Particle emission: LOW

LOAD-BEARING CAPACITY

Up to 3 kg per m².

AMBIENT CONDITIONS

Can withstand:
- constant RH 70% and 25°C
- periodic RH 90% and 30°C
- ambient temperatures of up to 50°C.

ACCESS TO INSTALLATIONS

Easy access to installation services
allowed using Knauf Danoline access
panels.

ROBUSTNESS

Glass fibre reinforced gypsum. High
pressure resistance. Highly stable
ceiling ensured by tile density.