

VISIONA

DEMOUNTABLE ACOUSTICAL CEILING

- ✓ Directional ceiling look
- ✓ Light fixtures moved without demounting tiles
- ✓ Easily adapted to changing room purposes




FEATURES

- T-grid ceiling
- Rectangular ceiling tiles
- Installation in double T-grid
- Installation from below the T-grid

RECYCLABLE PRODUCT:

- Made of gypsum
- Danish Indoor Climate Labelling
- Improved indoor climate
- Repaintable without loss of acoustics
- Product is recyclable and can be reused in the production of new gypsum boards and gypsum tiles

PRODUCT SPECIFICS

EDGE DESIGN	 <p>EDGE E lengthwise Lay-in tile in recessed grid lengthwise</p>  <p>EDGE B crosswise No cross tees between tiles crosswise</p>
PERFORATION DESIGN Also available without perforations (Regula)	 <p>TANGENT Obround 4 x 14 mm c/c 10/20 mm</p>
PERFORATION MEASURES	
PERFORATION %	21.3%
NRC, @ 200mm, no mineral wool	0.75
NRC, @ 200mm, 50mm mineral wool	0.90
ALPHA-W, @ 200mm, no mineral wool	0.80
ALPHA-W, @ 200mm, 50mm mineral wool	0.90
LIGHT REFLECTION	70.9%
TILE WEIGHT, kg/m²	7.6 kg/m ²
SIZES, mm	Standard 400 x 1200 x 12.5
	Other options 300-400 x 600-2400 x 12.5
SURFACE TREATMENT	Front: White acrylic paint, RAL 9003, gloss 5. Back: Acoustic felt backing. Available in other colours on request.
SYSTEM COMPONENTS	1) Gypsum ceiling tile, 2) T24/38 main runner, 3) Spacer bar, 4) DG clips, 5) Hangers
CERTIFICATES	1) Environmental product declaration, 2) FDES – life cycle analysis, 3) Danish Indoor Climate Labelling, 4) ISO 16000-9 Emission of VOCs, 5) UL-listed in accordance to R26164

PRODUCT PERFORMANCE

FIRE RATING

A2-s1, d0

AIR QUALITY

Indoor value: 10 days
Particle emission: LOW

AMBIENT CONDITIONS

Can withstand:
- constant RH 70% and 25°C
- ambient temperatures of up to 50°C.

LOAD-BEARING CAPACITY

Up to 1 kg pr. tile (at max. 2mm deflection)

ROBUSTNESS

Glass fibre reinforced gypsum. High pressure resistance. Highly stable ceiling ensured by tile density.